Doby Verrolec

Accessories

Threaded Rod, Splitter Pins & Strapping

- Growing range of HVAC Accessories are available.
- Threaded Rod, traditional tried and tested method for HVAC suspension.
- Strong, durable and robust available in four thread sizes.
- Slotted Banding low cost method for suspending fixed loads.
- Manufactured in high quality galvanised steel for anti-corrosion.
- Standard profile geometry allows the use of industry standard brackets
- Sheet Metal Fasteners for rapid assembly of ductwork splitters and air turns.



Threaded Rod

For use in most construction jobs and materials including concrete, brickwork and stone. Our threaded rods/bars are suitable for a variety of purposes, including industrial applications, as they are strong, durable and robust. We supply our Threaded Rod in standard 3m lengths across 4 sizes: M6, M8, M10 and M12.



Standard Lengths (Threaded Rod)

Threaded Rod Ref: Length
M6, M8, M10 & M12 3m lengths

Fasteners

Our Sheet Metal Fasteners allow for the rapid assembly of ductwork splitters and air turns. They also enable purpose made louvres to be fabricated in a fraction of the time of



traditional methods. Supplied in 2 variations, the DS513 (with green washer) and the 305 (with blue washer).

Slotted Banding



Doby Verrolec's 'DobyStrap' Slotted Banding is the perfect low cost method of suspending fixed loads such as rectangular and circular ductwork, pipe work and cabling. Slotted banding is manufactured using only the highest quality galvanised steel to prevent the possibility of corrosion. The banding is supplied in rolls of 30 metres.

Packing Details (Banding)

Length Bundle Size

30m Reel x 5 Reels



Packing Details (Fasteners)

Product code: Packing

DS513 (including green washer) x 1000 pieces/box

305 (including blue washer) x 100 pieces/box

309 (seal washer only) x 100 pieces/box

