

DobyGrip wire suspension units

- The DobyGrip wire suspension system, a perfect solution to suspending static loads.
- Reduces the installation time compared to conventional methods of suspension.
- Simple height adjustment using the external cable release, saves time and money!
- Zamac 5 zinc casting construction.
- Safety load tested to a 5:1 Safety Factor across all products.
- Available in three sizes, 1mm 2mm & 3mm.
- Seismic testing to 110,000 cycles at 10Hz independently tested by Northumbria University and witnessed by Lloyds Register.
- Suitable for use as shown in HVCA DW/144 Specification for Sheet Metal Ductwork Fig. 64-72.



Code	Description	Size	Packing
DG1	SWL 10 Kg rated grip	1mm	x 50 per bag
DG2	SWL 50 Kg rated grip	2mm	x 20 per bag
DG3	SWL 100 Kg rated grip	3mm	x 10 per bag

SWL: Safe Working Load

Loads tested to a 5:1 safety factor.
All ratings were determined by independent testing at Northumbria University and witnessed by Lloyds Register.

Wire with Loop

- Quick and easy fixing to purlins, beams etc by forming a choke knot.
- Reduces the installation time compared to conventional methods of suspension.
- All wires are supplied including the DobyGrip Lock.
- Galvanised steel construction (7x7 strands).
- Strict quality inspection procedures and independent tests ensure reliability.
- Available in three diameters and in 1m, 2m, 3m, 4m & 5m lengths.



Code	Description	Size/Length	Packing
DG11L	Loop ended wire	1mm x 1m	x10 per bag
DG12L	Loop ended wire	1mm x 2m	x10 per bag
DG13L	Loop ended wire	1mm x 3m	x10 per bag
DG14L	Loop ended wire	1mm x 4m	x10 per bag
DG15L	Loop ended wire	1mm x 5m	x10 per bag
DG21L	Loop ended wire	2mm x 1m	x10 per bag
DG22L	Loop ended wire	2mm x 2m	x10 per bag
DG23L	Loop ended wire	2mm x 3m	x10 per bag
DG24L	Loop ended wire	2mm x 4m	x10 per bag
DG25L	Loop ended wire	2mm x 5m	x10 per bag
DG31L	Loop ended wire	3mm x 1m	x10 per bag
DG32L	Loop ended wire	3mm x 2m	x10 per bag
DG33L	Loop ended wire	3mm x 3m	x10 per bag
DG34L	Loop ended wire	3mm x 4m	x10 per bag
DG35L	Loop ended wire	3mm x 5m	x10 per bag

Loads tested to a 5:1 safety factor.
All ratings were determined by independent testing at Northumbria University and witnessed by Lloyds Register.

Wire on Reels

- For suspending various products and services using the DobyGrip.
- Available in three diameters, 1mm, 2mm & 3mm.
- Galvanised steel construction (7x7 strands).
- 150 metres (492 feet) supplied on strong plastic reel.
- Strict quality inspection procedures and independent tests ensure reliability.

Code	Description	Size/Length
DGWR1	Reel wound wire	1mm x 150m
DGWR2	Reel wound wire	2mm x 150m
DGWR3	Reel wound wire	3mm x 150m
DGWC	Wire Rope Cutters	N/A



For use with static loads only.

When cutting wire rope for insertion into the DobyGrip unit it is important to use the correct tool. The Draper Wire Cutter will ensure that the form of the rope will be maintained prior to insertion within the unit.

